

Lectrosonics IFBT2.0



At this year's InfoComm 2026 in Las Vegas (North Hall, Booth N7270,) Lectrosonics announces that the IFB (Interruptible FoldBack) transmitter base station, the IFBT2.0, is now shipping. The unit is in a ½ rack chassis and features two independent transmitters, equaling the rack density of the older T4 unit. The IFBT2.0 has enhanced, menu-selectable input connectivity including analog line and mic level, Dante and AES digital, Clear-com, and RTS. The inputs are compatible with “wet” signals, allowing for use with connections where DC is present on the audio lines. The IFBT2.0 also includes USB-C and Ethernet connections for use with Wireless Designer software for system monitoring, frequency coordination, and setup.

The IFBT2.0 offers IFB, NU Hybrid, and EU Hybrid compatibility modes so that the unit can be used in IFB and other applications including point-to-point audio where audio fidelity is critical. The next-generation transmitter unit is fully compatible with the existing line of IFBR1B, IFBR1C (IFBlue), legacy IFBR1, and IFBR1A receivers; and all Digital Hybrid Wireless and current digital Lectrosonics receivers from the Venue 2 to LR, DSQD, DCR822, and DSR4. Three tuning ranges are available for the new IFBT2.0: A1 (470-537 MHz), B1 (537-614 MHz) and C1 (614-692 MHz). These versions exactly match the currently available IFBR1B and IFBR1C (IFBlue) receiver packs and together cover the available UHF TV frequencies for most regions.

The IFBT2.0 offers user selectable RF power settings at 10, 25, 50, 100, and 250 mW (North American versions), and 10, 25, and 50 mW (EU versions). A circulator/isolator is employed on each channel, allowing RF signals to pass through to the antennas, while blocking external signals from entered the transmitter output sections. This greatly reduces the generation of intermodulation products.

Future firmware updates can be installed in the IFBT2.0 in the field via the USB-C jack on the front panel of the unit. The unit comes standard with rack mounting hardware and can be co-racked with Lectrosonics M2T or DSQD units or racked singly with the optional RMPRM2T-1 kit. The front panel features a color LCD for menu navigation and monitoring, and tactile buttons for ease of use and longevity.

“The initial reactions to the new IFB base-station transmitter have been fantastic,”

Lectrosonics announces IFBT2.0 Interruptible Foldback Transmitter Base Station

Friday, 12 June 2026 15:55

states Karl Winkler, EVP of Product Design & Distribution at Lectrosonics. “Now that we have completed our initial production runs and received FCC, RCM, and CE certifications, our first rounds of customer orders have already shipped.”

The IFBT2.0 IFB base station will be exhibited at the InfoComm show in Las Vegas, NV, June 17-19, 2026 at booth #N7270 in the North Hall. For pricing and availability, contact your authorized Lectrosonics retailer.

www.lectrosonics.com