Celestion CF1025BMB

A 10-inch Bass/Midbass Cast Aluminum Pro Audio Loudspeaker



Celestion, a supplier of professional loudspeakers and compression drivers for sound reinforcement applications, announces the introduction of the CF1025BMB 10-inch (254mm) diameter ferrite magnet, cast aluminum chassis professional audio driver. Well-suited to both bass and mid-bass applications, the new CF1025BMB particularly excels as a bass unit in compact subwoofer applications.

The Celestion CF1025BMB features a 2.5"/64mm multi-layer voice coil providing 300W (AES standard) power handling and 92.5 dB sensitivity with an output frequency range of 45Hz to 5000Hz. The elastomer surround enables a longer Xmax compared to a conventional 10" mid-bass speaker, allowing the CF1025BMB to better reproduce lower frequencies. This makes the driver a natural solution for discreet, compact subwoofer applications. However, it also performs very smoothly up to 2kHz, making the CF1025BMB a superb option for 2-way designs with the added advantage of exceptional low frequency performance.

Tuesday, 17 May 2022 12:21

In addition to the extended low frequency performance, features include Celestion's smart airflow vented magnet assembly for dynamic heat dispersion to minimise power compression during operation; and an optimised T-pole magnet assembly to maximise the stability of cone movement for enhanced BI symmetry, hence lower distortion.

Developed at Celestion's headquarters in Ipswich, England, this loudspeaker is designed using specialist in-house software deploying FEA (Finite Element Analysis) modelling techniques, enabling the Celestion engineering team rapidly to achieve genuine increases in performance, that translate into greater product longevity, and exceptionally low distortion.

This new high-performance cast aluminium loudspeaker is another example of Celestion's continuing commitment to delivering a wide range of high-quality solutions for sound reinforcement and professional audio applications.

www.celestion.com