

Focal unveils the Alpha 50 Evo and Alpha 65 Evo



Dedicated to music creation and all reproduction, the Alpha 50 Evo and Alpha 65 Evo guarantee excellent sound coherence, no matter where you're listening. For renewed performance, Focal has chosen an aluminium inverted dome tweeter to ensure vast sound dispersion, as well as the Slatefiber cone. This recycled carbon cone, produced exclusively by the French brand at its Saint-Étienne workshops, has been chosen for its neutrality and dynamics. Focal is constantly renewing its offering, drawing on its acoustics expertise of over 40 years and its innovation capacity. This is demonstrated by the new large laminar port, which limits distortion noise.

The Alpha Evo monitors boast a new 1/4" (6.35mm) TRS jack input - in addition to the XLR and RCA analogue inputs -, a disengageable automatic stand-by mode and inserts for wall and ceiling fastening: a truly versatile range (Mix, Mastering, DJ, Broadcast). In terms of amplification, the monitors are each equipped with two class D amplifiers. The high current capacity of these allows full control of the signal dynamics. It also allows high volumes to be reached without distortion. Each of the loudspeakers picks up the smallest details in the mix, across all musical styles.

Focal unveils the Alpha 50 Evo and Alpha 65 Evo

Friday, 26 March 2021 09:56



The monitors feature a 5/8" (15mm) -thick MDF cabinet, and incorporate internal braces to ensure it is highly robust, even at the highest levels of acoustic pressure. The bass-reflex design has been used to ensure easy acoustic integration in even the most cramped spaces. In terms of aesthetics, the traditional cube monitor shape makes way for rounded contours. The side panels create a sophisticated, robust and modern design which contributes to excellent acoustics and a unique and harmonious signature across the collections.

Key points

- Excellent dynamics
- Wide dispersion enabling the same sound to be maintained throughout the entire room
- Slatefiber cone manufactured in France: sound neutrality, no distortion
- Identical tonal balance at both low and high volume
- Connect up to 3 audio sources
- Inserts for wall fastening
- Protective grills included

Technical Specifications

Alpha 50 Evo Monitoring

- Frequency response (+/- 3dB): 45Hz - 22kHz
- Maximum SPL: 101dB SPL (peak @393/8" (1m))
- Power supply: 100 - 240V~(T2AL fuse/250V)
- Stand-by consumption: <0.5W
- Woofer: 5" (13cm) Slatefiber cone
- Tweeter: 25mm (1") with aluminium inverted dome
- Construction: 0.6" (15mm) MDF

Alpha 65 Evo Monitoring

- Frequency response (+/- 3dB): 40Hz - 22kHz
- Maximum SPL: 104dB SPL (peak @393/8" (1m))
- Power supply: 100 - 240V~(T2AL fuse/250V)
- Stand-by consumption: <0.5W
- Woofer: 6.5" (16.5cm) Slatefiber cone
- Tweeter: 25mm (1") with aluminium inverted dome
- Construction: 0.6" (15mm) MDF
- Dimensions with 4 rubber feet (HxWxD): 13.35 x 10.28 x 11.38" (339 x 261 x 289 mm)
- Weight: 16.8lbs (7.6kg)

www.sound-service.eu

www.focal.com