

# Zoom LiveTrak L6max



Zoom announces the LiveTrak L6max 12-channel digital mixer / 14-track 32-bit float multitrack recorder. The LiveTrak L6max takes the concept of the popular LiveTrak L6 to the next level. Not only does it feature two additional XLR/jack combo inputs, but it also integrates groundbreaking AI Noise Reduction and enables unlimited overdubbing, including a separate “bounce track” - new features that are unique in its class. The L6max can be installed in a Eurorack case using the optional rack mount adapter kit, and it can be powered by batteries, a USB power bank or AC power.

With 12 discrete tracks (plus stereo mix), clip-free 32-bit float audio, AI Noise Reduction, effects, two headphone outputs with separate feeds, MIDI, and sound pads, it's perfect for bands, live sets of electronic music, live streaming, podcasting, and more. The L6max offers four XLR/jack combo inputs with +48 V phantom power, two of which are also suitable for Hi-Z instruments. The four stereo line inputs now feature switchable -20 dB PADs for direct connection of older synthesizers or Eurorack modules.

Each channel features a 3-band EQ with tunable mids, two external aux sends, pan, an effects send and a sub-mix send for a second, separate headphone mix. The master signal can be refined with a compressor. You can connect, programme and synchronise the L6max with external MIDI equipment via the 3.5 mm MIDI input or with a computer via USB. The four sound pads can be used to trigger pre-recorded samples or for live sampling during a performance and they can also be

synchronised with MIDI. The L6max can also be used as a 32-bit float 12-in/4-out USB audio interface on a computer, iOS, or Android device while simultaneously recording to an SD card. And the new OLED display provides a clear overview at all times and makes operation easier, even in dark environments.

The LiveTrak L6max will ship in late Q4 2025.

### Features:

- 12-channel digital mixer
- 14-track 32-bit float multitrack recorder with unlimited overdubbing and special 'bounce track'
- Optional Eurorack mounts
- 4 XLR/jack combo inputs (2 with Hi-Z )
- +48V phantom power
- 4-stereo ¼" inputs with -20dB PAD
- 2 aux sends
- 1 headphone out
- 1 sub headphone out with individual mix
- 2 balanced main outs
- 3-band EQ per channel
- AI Noise Reduction
- Built-in send effects
- Advanced Compressor
- 128x64 OLED Display
- MIDI In/Out
- MIDI sync and MIDI controller functions
- 4 Soundpads with sampling function for remixing
- L6 Editor Software
- Power Supply, Battery or USB powered
- Can be used as 12 in 4 USB-C audio interface with simultaneously recording to SD card
- Records to microSD cards up to 2TB

[www.sound-service.eu](http://www.sound-service.eu)